



16	Bushing(TOP)	PBT	1	577C Green Color
15	Bushing(DOWN)	PBT	1	701C Pink Color
14	Sleeve(Barrel)	Low lead Brass Rod	2	Nickel Plated
13	Metal Shell	0.2T Phosphor Copper	1	Silver Plated
12	Cover	PBT	1	Black Color
11	Housing	PBT	1	Black Color
10	Tip Lead(TOP)	0.4T Brass	1	Silver Plated
9	Tip Spring(TOP)	0.25T Phosphor Copper	1	Silver Plated
8	Ring Lead(TOP)	0.4T Brass	1	Silver Plated
7	Ring Spring(TOP)	0.25T Phosphor Copper	1	Silver Plated
6	Earth Terminal(TOP)	0.4T Phosphor Copper	1	Silver Plated
5	Tip Spring(DOWN)	0.25T Phosphor Copper	1	Silver Plated
4	Break Terminal(DOWN)	0.4T Bronze	1	Silver Plated
3	Break Terminal(DOWN)	0.4T Bronze	1	Silver Plated
2	Ring Spring(DOWN)	0.3T Phosphor Copper	1	Silver Plated
1	Earth Terminal(DOWN)	0.4T Phosphor Copper	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	09.18.2020	王平華			

PART NAME : 3.5φ PHONE JACK	PART NUMBER: SCJ351M5NUSGBN4L	VERSION: 1.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

