



Pin Hole Layout  
(Jack Bottom View)

NO.	Description	Material	Q'TY	Finish
8.	Washer	0.5T Steel	1	Nickel Plated
7.	Nut	2.0T Steel	1	Nickel Plated
6.	Cover	PC	1	Transparent
5.	Housing	PBT	1	Black Color
4.	Metal Ring	Brass	1	Nickel Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.3T Phosphor Bronze	1	Silver Plated

	<b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.				
	DATE	DWN	CHKD	APVD	MANAGER
		10.12.2011			

PART NAME : 6.3φ PHONE JACK	PART NUMBER: SCJ624R0NAS1B00G	VERSION: 3.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

**SPECIFICATIONS:**  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

RoHS Compliant  
 For Reference 僅供參考