



Pin Hole Layout  
(Jack Bottom View)

7.	Nut	Low lead Brass Rod	1	Nickel Plated
6.	Cover	PC	1	Transparent
5.	Housing	POM	1	Black Color
4.	Barrel	Low lead Brass Rod	1	Nickel Plated
3.	Break Terminal	0.3T Brass	1	Silver Plated
2.	Tip Spring	0.2T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.3T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

<b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	09.08.2020	王平華			

PART NAME : 3.5∅ PHONE JACK	PART NUMBER: SCJ328M1NYS1B00L	VERSION: 1.0
-----------------------------	-------------------------------	--------------

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1
---	----------	------------

SPECIFICATIONS:  
 Contact Resistance : 30mΩ max  
 Insulation Resistance: 100MΩ min. at DC 500V  
 Remark: ▲: The Most Important Dimension

For Reference  
僅供參攷

RoHS&SVHC  
Compliant