



Pin Hole Layout
(Jack Bottom View)

5.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
4.	Shunt Terminal	0.3T Bronze	1	Silver Plated
3.	Shunt Terminal	0.2T Bronze	1	Silver Plated
2.	Earth Terminal	0.2T Phosphor Bronze	2	Silver Plated
1.	Housing	PA9T	1	Black Color
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	09.02.2020	王平華			

PART NAME: 3.5 ϕ PHONE JACK	PART NUMBER: SCJ315P00USOB00G	VERSION: 4.0
TOLERANCE: ± 0.3 mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30m Ω max.
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension

For Reference
僅供參攷

RoHS&SVHC
Pb Free Process