



Pin Hole Layout
(Jack Bottom View)

8.	Insulator R(T&D)	PBT	2	White Color
7.	Insulator L(T&D)	PBT	2	Red Color
6.	Housing	ABS	1	Black Color
5.	Cover	ABS	2	Black Color
4.	Metal Plate	0.2T Bronze	2	Nickel Plated
3.	Terminal T	0.5T Brass	2	Silver Plated
2.	Terminal D	0.5T Brass	2	Silver Plated
1.	Earth Terminal	0.5T Brass	2	Nickel Plated
NO.	Description	Material	Q'TY	Finish

RoHS Compliant For Reference
僅供參考

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

广东科斯达电子科技有限公司
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
06.29.2010				

PART NAME : PIN JACK	PART NUMBER: SCP6961NS223300G	VERSION:3.0
TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm	SCALE:1/1