



Pin Hole Layout  
(Jack Bottom View)

7.	Insulator	PBT	3	White Color
6.	Insulator	PBT	3	Red Color
5.	Terminal D	0.5T Brass	3	Silver Plated
4.	Terminal T	0.5T Brass	3	Silver Plated
3.	Earth Terminal	0.5T Brass	3	Nickel Plated
2.	Cover	ABS	3	Black Color
1.	Housing	ABS	1	White Color
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司  
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
05.19.2006				

PART NAME : PIN JACK

PART NUMBER:SCP6973NS232323G

VERSION:2.0

TOLERANCE : $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE:1/1

SPECIFICATIONS:

Contact Resistance : 30m $\Omega$  max  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark: ▲ : The Most Important Dimension

RoHS  
Compliant

For Reference  
僅供參考