



Pin Hole Layout  
Jack Bottom View

For Reference  
僅供參考

RoHS&SVHC  
Compliant

NO.	Description	Material	Q'TY	Finish
5.	Cover	PBT+30%	1	Black Color
4.	Housing	PBT+30%	1	Black Color
3.	Pin Terminal	0.3T Brass	1	Silver Plated
2.	Sleeve Spring	0.3T Berylium	1	Silver Plated
1.	Pin(1.3φ)	0.3T Brass	1	Silver Plated

<b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	09.22.2021	王平華			

PART NAME : DC POWER JACK	PART NUMBER: SCD410ACS000B00G	VERSION: 10.0
---------------------------	-------------------------------	---------------

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm		SCALE:1/1
---	---------	--	-----------

SPECIFICATIONS:  
 Contact Resistance : 30m Ωmax  
 Current Rating : Max 5A , 24V DC  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension