



Pin Hole Layout
(Jack Bottom View)

| | | | | |
|-----|------------------------|------------|------|---------------|
| 8. | Washer | PBT | 1 | Red Color |
| 7. | Washer | PBT | 1 | White Color |
| 6. | Cover | ABS | 1 | Black Color |
| 5. | Base | ABS | 1 | White Color |
| 4. | Metal Plate | 0.2T Brass | 1 | Nickel Plated |
| 3. | Terminal T | 0.5T Brass | 1 | Silver Plated |
| 2. | Terminal D | 0.5T Brass | 1 | Silver Plated |
| 1. | Earth Terminal(Barrel) | 0.5T Brass | 1 | Nickel Plated |
| NO. | Description | Material | Q'TY | Finish |

| | | | | | |
|--|------------|-----|------|------|---------|
| 广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE | DWN | CHKD | APVD | MANAGER |
| | 09.06.2006 | | | | |

| | | |
|----------------------|-------------------------------|-------------|
| PART NAME : PIN JACK | PART NUMBER: SCP6823NS320000G | VERSION:5.0 |
|----------------------|-------------------------------|-------------|

| | | |
|--|---------|-----------|
| TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT:mm | SCALE:1/1 |
|--|---------|-----------|

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

RoHS Compliant For Reference
 僅供參考