



| 8. | Washer L&R (D) | PBT | 2 | Red Color |
|-----|------------------------|------------|------|---------------|
| 7. | Washer L&R (T) | PBT | 2 | White Color |
| 6. | Metal Plate | 0.2T Brass | 2 | Nickel Plated |
| 5. | Cover | ABS | 2 | Black Color |
| 4. | Base | ABS | 1 | White Color |
| 3. | Terminal T | 0.5T Brass | 2 | Silver Plated |
| 2. | Terminal D | 0.5T Brass | 2 | Silver Plated |
| 1. | Earth Terminal(Barrel) | 0.5T Brass | 2 | Nickel Plated |
| NO. | Description | Material | Q'TY | Finish |

Pin Hole Layout
(Jack Bottom View)

| | | | | | |
|---|------------|-----|------|------|---------|
| 广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE | DWN | CHKD | APVD | MANAGER |
| | 12.20.2005 | | | | |

| | | |
|---|-------------------------------|-------------|
| PART NAME : PIN JACK | PART NUMBER: SCP6843NS323200G | VERSION:3.0 |
| TOLERANCE : ± 0.3 mm UNLESS OTHERWISE SPECIFIED | | UNIT:mm |
| | | SCALE: |

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension

RoHS Compliant For Reference
僅供參考