



Pin Hole Layout  
(Jack Bottom View)

8.	Washer T(L&R)	PBT	2	White Color
7.	Washer D(L&R)	PBT	2	Red Color
6.	Housing	ABS	1	White Color
5.	Cover	ABS	2	Black Color
4.	Metal Plate	0.2T Bronze	2	Nickel Plated
3.	Terminal T	0.5T Brass	2	Silver Plated
2.	Terminal D	0.5T Brass	2	Silver Plated
1.	Earth Terminal (Barrel)	0.4T Brass	2	Nickel Plated
NO.	Description	Material	Q'TY	Finish

	<b>广东科斯达电子科技有限公司</b> GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		08.14.2006				

PART NAME : PIN JACK	PART NUMBER : SCP6883NS3232T2G	VERSION:3.0
TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED		UNIT:mm
		SCALE:1/1

SPECIFICATIONS:  
 Contact Resistance :  $30\text{m}\Omega$  max  
 Insulation Resistance :  $100\text{M}\Omega$  min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark: ▲ : The Most Important Dimension

RoHS Compliant  
 For Reference  
 僅供參考