



| 11. | Insulator R | PBT | 2 | Yellow Color |
|-----|------------------------|-------------|------|---------------|
| 10. | Insulator C | PBT | 2 | White Color |
| 9. | Insulator L | PBT | 2 | Red Color |
| 8. | Earth Terminal (DIN) 2 | 0.3T Bronze | 1 | Nickel Plated |
| 7. | Terminal D | 0.4T Bronze | 3 | Silver Plated |
| 6. | Terminal T | 0.4T Bronze | 3 | Silver Plated |
| 5. | Earth Terminal R | 0.4T Bronze | 1 | Nickel Plated |
| 4. | Earth Terminal L | 0.4T Bronze | 1 | Nickel Plated |
| 3. | Earth Terminal (DIN) 1 | 0.4T Bronze | 1 | Nickel Plated |
| 2. | Terminal (DIN) | 0.4T Bronze | 8 | Silver Plated |
| 1. | Housing | PPO | 1 | Black Color |
| NO. | Description | Material | Q'TY | Finish |

| | | | | | | |
|--|---|------------|-----|------|------|---------|
| | 广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE | DWN | CHKD | APVD | MANAGER |
| | | 02.12.2007 | | | | |

| | | |
|---|-------------------------------|--------------|
| PART NAME : MINI DIN JACK & PIN JACK | PART NUMBER: SCP903S4BS0N234G | VERSION: 4.0 |
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT: mm | SCALE: 1/1 |

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

RoHS Compliant
 僅供參考