



Pin Hole Layout
(Jack Bottom View)

| | | | | | |
|-----|------------------|------------------|-----------|-----------------|-------------|
| 6. | Insulator | Bakelite | 1 | Black Color | |
| 5. | Insulator | PBT | 1 | Black Color | |
| 4. | Insulator | PBT | 1 | 1795C Red Color | |
| 3. | Pin | 0.25T Brass | 1 | Tin Plating | |
| 6 | 2. | Mounting Bracket | 0.4T Iron | 1 | Tin Plating |
| 1. | Phone Jack Shell | 0.3T Brass | 1 | Nickel Plating | |
| NO. | Description | Material | Q'TY | Finish | |

SPECIFICATIONS:
 See "Details of Environment-Related Substance"
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

广东科斯达电子科技有限公司
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

DATE DWN CHKD APVD MANAGER

06.22.2005

黄志勇

陈素芳

李国平

700 6-23
黄志勇

PART NAME : PIN JACK

PART NUMBER: SCP606UNT2T0100

VERSION:1.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE: /