



8.	Insulator	PBT	3	White Color
7.	Insulator	PBT	3	Red Color
6.	Terminal D	0.5T Brass	3	Silver Plated
5.	Terminal T	0.5T Brass	3	Silver Plated
4.	Metal Plate	0.2T Bronze	3	Nickel Plated
3.	Earth Terminal	0.5T Brass	3	Nickel Plated
2.	Cover	ABS	3	Black Color
1.	Housing	ABS	1	White Color
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	08.14.2006				

PART NAME : PIN JACK	PART NUMBER: SCP6983NS232323G	VERSION: 2.0
TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

Pin Hole Layout (Jack Bottom View)

KSD

2-1.70*3.70

1 2 3 6 5 9 8 1

7.20 7.70 10.45 11.70

8.00 20.00 28.00 36.00 40.70

9- $\phi 1.20$

RoHS Compliant **For Reference 僅供參考**

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension