



Pin Hole Layout  
(Jack Bottom View)

| 3.  | Housing        | PBT        | 1    | Black Color   |
|-----|----------------|------------|------|---------------|
| 2.  | Pin            | 0.6T Brass | 1    | Silver Plated |
| 1.  | Earth Terminal | 0.4T Brass | 1    | Nickel Plated |
| NO. | Description    | Material   | Q'TY | Finish        |

RoHS  
Compliant

For Reference  
僅供參考

SPECIFICATIONS:

Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

广东科斯达电子科技有限公司  
 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

|            |     |      |      |         |
|------------|-----|------|------|---------|
| DATE       | DWN | CHKD | APVD | MANAGER |
| 12.12.2005 |     |      |      |         |

PART NAME : PIN JACK      PART NUMBER: SCP627UNS100000G      VERSION: 2.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED      UNIT: mm      SCALE: 1/1