



10.	Center Contact	0.4T Brass	8	Silver Plated
9.	Tip Contact	0.2T Phosphor Bronze	2	Silver Plated
8.	Break Contact	0.3T Phosphor Bronze	2	Silver Plated
7.	Outer Contact	0.4T Brass	10	Nickel Plated
6.	Sealed Plate	0.2T SUS304	1	
5.	Washer	PBT	2	Green color
4.	Washer	PBT	2	Blue color
3.	Washer	PBT	2	White color
2.	Washer	PBT	4	Red color
1.	Housing	PA66+33%GF	1	Black Color
NO.	Description	Material	Q'TY	Finish

广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
	11.18.2009				

PART NAME:PIN JACK	PART NUMBER:SCP914WNS752320G	VERSION:3.0
--------------------	------------------------------	-------------

TOLERANCE:±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm	SCALE:1/1
---	---------	-----------

SPECIFICATIONS:
 Contact Resistance :30mΩ max
 Insulation Resistance :100MΩ min.at DC500V
 Dielectric Withstand Voltage:AC 500V for one minute
 Remark:▲:The Most Important Dimension

RoHS
 Pb Free Process
 For Reference
 僅供參考