



9	Washer	0.5T Steel	1	Nickel Plated
8	Nut	2.0T Steel	1	Nickel Plated
7	Insulator	Red Vulcanited Fibre	1	Red Color
6	Bushing	Brass	1	Nickel Plated
5	Barre(W/Thread)	PC	1	Black Color
4	Cover	0.5T Steel	1	Nickel Plated
3	Housing	POM	1	Black Color
2	Ring Spring	0.35T Phosphor Bronze	1	Silver Plated
1	Tip Spring	0.35T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

	广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	DATE	DWN	CHKD	APVD	MANAGER
		10.12.2011				

PART NAME : 6.3 ϕ PHONE JACK	PART NUMBER: SCJ618R3NAS1B11G	VERSION: 3.0
TOLERANCE : ± 0.3 mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension

RoHS Compliant

For Reference
僅供參考