



|     |                 |                       |      |               |
|-----|-----------------|-----------------------|------|---------------|
| 9   | Washer          | 0.5T Steel            | 1    | Nickel Plated |
| 8   | Nut             | 2.0T Steel            | 1    | Nickel Plated |
| 7.  | Insulator       | Red Vulcanited Fibre  | 1    | Red Color     |
| 6.  | Bushing         | Brass                 | 1    | Nickel Plated |
| 5.  | Barre(W/Thread) | PC                    | 1    | Black Color   |
| 4.  | Cover           | 0.5T Steel            | 1    | Nickel Plated |
| 3.  | Housing         | POM                   | 1    | Black Color   |
| 2.  | Ring Spring     | 0.35T Phosphor Bronze | 1    | Silver Plated |
| 1.  | Tip Spring      | 0.35T Phosphor Bronze | 1    | Silver Plated |
| NO. | Description     | Material              | Q'TY | Finish        |

M12XP1.0 METRIC THREAD

|  |   |            |     |      |      |         |
|--|---|------------|-----|------|------|---------|
|  | <b>广东科斯达电子科技有限公司</b><br>GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD. | DATE       | DWN | CHKD | APVD | MANAGER |
|  |   | 10.12.2011 |     |      |      |         |

|   |                               |              |
|---|-------------------------------|--------------|
| PART NAME : 6.3φ PHONE JACK                   | PART NUMBER: SCJ618RONAS1B21G | VERSION: 3.0 |
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT: mm                      | SCALE: 1/1   |

**SPECIFICATIONS:**  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

RoHS Compliant  
 符合RoHS  
 For Reference  
 仅供参考