



Material (材質)

- (端子座) TERMINAL BASE:PA 66(UL 94V-0)
- (柄) ACTUATOR:PA66(UL 94V-0)
- (彈簧) SPRING:STAINLESS STEEL WIRE
- (接觸片) CONTACT: SILVER PLATED COPPER ALLOY
- (端子) TERMINAL: SILVER PLATED COPPER ALLOY
- (接點) CONTACT: Ag ALLOY

SPECIFICATION 規格:



Rating 額定:

- 16A/26A 125/250VAC 40T125(UL;CUL)
- 16A 42VDC 40T125(UL;CUL;CQC;EMEC17;NEMKO)
- 16A/20A 125/ 250VAC 40T125(CQC;EMEC17;NEMKO)

Electrical (電氣性能)

- (接觸電阻) CONTACT RESISTANCE:50mΩ Max
- (絕緣電阻) INSULATION RESISTANCE:100MΩ Min ,AT 500VDC
- (耐電壓) DIELECTRIC STRENGTH:1500VAC 1 MINUTE
- (電氣壽命) ELECTRICAL LIFE:10, 000 CYCLES

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	Above 5 ~ 15 ±0.3	Above 15 ~ 30 ±0.4	Above 30 ~ 50 ±0.5	Angle ±0.3°	3RD. ANGEL'S	UNITS	MM
------------------------------------	--------------	-------------------	--------------------	--------------------	-------------	--------------	-------	----

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Ming Ming Zou	07/10/13	FINISH	MODLE	ENCODER
CHECKED BY:	DATE	SCALE	DWG NO.	KSD-FR04-302B3Q16L-T
Ning Ning Su	07/10/13	SHEET NO.	PART NO.	
APPROVED BY:	DATE			
Jia Xiang	07/10/13			

ITEM NO.	DESCRIPTION	DRAWN	DATE