



**Material (材質)**

- (端子座) TERMINAL BASE: PA 66(UL 94V-0)
- (柄) ACTUATOR: PA66(UL 94V-0)
- (彈簧) SPRING: STAINLESS STEEL WIRE
- (接觸片) CONTACT: SILVER PLATED COPPER ALLOY
- (端子) TERMINAL: SILVER PLATED COPPER ALLOY
- (接點) CONTACT: Ag ALLOY

**SPECIFICATION 規格:**



**Rating 額定:**

- 16A/26A 125/250VAC 40T125(UL;CUL)
- 16A 42VDC 40T125(UL;CUL;CQC;EMEC17;NEMKO)
- 16A/20A 125/ 250VAC 40T125(CQC;EMEC17;NEMKO)

**Electrical (電氣性能)**

- (接觸電阻) CONTACT RESISTANCE: 50mΩ Max
- (絕緣電阻) INSULATION RESISTANCE: 100MΩ Min ,AT 500VDC
- (耐電壓) DIELECTRIC STRENGTH: 1500VAC 1 MINUTE
- (電氣壽命) ELECTRICAL LIFE: 10, 000 CYCLES

**广东科斯达电子科技有限公司**  
**GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.**

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Ming Ming Zou	07/10/13	FINISH	MODLE	ENCODER
CHECKED BY:	DATE	SCALE	DWG NO.	KSD-FR04-201B3Q16L-S
Ning Ning Su	07/10/13	SHEET NO.	PART NO.	
APPROVED BY:	DATE			
Jia Xiang	07/10/13			

ITEM NO.	DESCRIPTION	DRAWN	DATE