



**SPECIFICATION 规格:**

**Rating 额定:**

8A 125/250VAC (UL,CUL)  
12A-8(3)A250V-μT125/55(ENEC17,CQC)

**Material (材質)**



- (柄) ACTUATOR: PA66+30%GF(UL 94V-0)
- (上盖) CAP: PA66(UL 94V-0)
- (基座) BASE: PA66(UL 94V-0)
- (端子) TERMINAL: BRASS/COPPER ALLOY SILVER PLATED

**Electrical (电气性能)**

- (接触电阻) INITIAL CONTACT RESISTANCE: 50mΩ Max
- (操作力量) OPERATION FORCE: 600±300gf/1300±500gf/1000±3000gf
- (绝缘电阻) INSULATION RESISTANCE: 100MΩ Min 500VDC
- (耐电压) WITHSTAND VOLTAGE: 1KVAC FOR 1 MINUTE
- (电气寿命) ENDURANCE: 10,000 CYCLES Min

**广东科斯达电子科技有限公司**  
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Ming Ming Zou	07/10/13	FINISH	MODLE	ENCODER
CHECKED BY:	DATE	SCALE	DWG NO.	K50-A
Ning Ning Su	07/10/13	SHEET NO.	PART NO.	K50-A
APPROVED BY:	DATE			
Jia Xiang	07/10/13			

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE	A4
VER	A