

Material (材質)

- (端子座) TERMINAL BASE:PA 66(UL 94V-0)
- (柄) ACTUATOR:PA66(UL 94V-0)
- (彈簧) SPRING:STAINLESS STEEL WIRE
- (接觸片) CONTACT: SILVER PLATED COPPER ALLOY
- (端子) TERMINAL: SILVER PLATED COPPER ALLOY
- (接點) CONTACT: Ag ALLOY

SPECIFICATION 規格:





Rating 額定:

- 16A/26A 125/250VAC 40T125(UL;CUL)
- 16A 42VDC 40T125(UL;CUL;CQC;EMEC17;NEMKO)
- 16A/20A 125/ 250VAC 40T125(CQC;EMEC17;NEMKO)

Electrical (電氣性能)

- (接觸電阻) CONTACT RESISTANCE:50mΩ Max
- (絕緣電阻) INSULATION RESISTANCE:100MΩ Min ,AT 500VDC
- (耐電壓) DIELECTRIC STRENGTH:1500VAC 1 MINUTE
- (電氣壽命) ELECTRICAL LIFE:10, 000 CYCLES



广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Ming Ming Zou
 DATE: 07/10/13
 CHECKED BY: Ning Ning Su
 DATE: 07/10/13
 APPROVED BY: Jia Xiang
 DATE: 07/10/13

MAT'L		TITLE	ENCODER
FINISH		MODLE	ENCODER
SCALE	1:1	DWG NO.	KSD-FR04-322B3Q16L-S
SHEET NO.	1 of 1	PART NO.	

SIZE A4
 VER A