


产品型号		GDTX60U-M/-F (UL认证)	
额定电流	60A	瞬间电流	120A
接触电阻	0.45mΩ	额定电压	DC500V
金属材质	铜镀金	绝缘材质	PA
工作温度	-20°C to 120°C	阻燃等级	UL94 V0
推荐线规	12AWG	推荐使用次数	100tims

**广东科斯达电子科技有限公司**  
KSDKG Guang dong Keside Electronic Technology Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: Ming Ming Zou DATE: 6/8/23  
CHECKED BY: Ning Ning Su DATE: 6/8/23  
APPROVED BY: Jia Xiang DATE: 6/8/23

MAT'L		TITLE	JACK
FINISH		MODLE	TX connector
SCALE	1:1	DWG NO.	KSD-TX-90WT-S4-G
SHEET NO.	1 of 1	PART NO.	

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新材質	Jack	050420
3	更新尺寸	Jack	121119
2	更新尺寸標示位置	Jack	082719
1	更新尺寸	Jack	080519

SIZE A4  
VER R4