



Pin No.	A	B	C	D
4	1.50	5.50	6.05	2.55
6	2.50	6.50	7.05	3.55
8	3.50	7.50	8.05	4.55
10	4.50	8.50	9.05	5.55
12	5.50	9.50	10.05	6.55
14	6.50	10.50	11.05	7.55
18	8.50	12.50	13.05	9.55
20	9.50	13.50	14.05	10.55
22	10.50	14.50	15.05	11.55
24	11.50	15.50	16.05	12.55
26	12.50	16.50	17.05	13.55
28	13.50	17.50	18.05	14.55
30	14.50	18.50	19.05	15.55
32	15.50	19.50	20.05	16.55
34	16.50	20.50	21.05	17.55
36	17.50	21.50	22.05	18.55
40	19.50	23.50	24.05	20.55
45	22.00	26.00	26.55	23.05
50	24.50	28.50	29.05	25.55
54	26.50	30.50	31.05	27.55
60	29.50	33.50	34.05	30.55

- NOTES:
- MATERIAL:
 - HOUSING: LCP,UL 94V-0
 - COVER: LCP,UL 94V-0
 - CONTACT: PHOSPHOR BRONZE
 - STATOR: BRASS
 - PLATING:
 - CONTACT: GOLD OR TIN PLATED ON NICKEL OVERALL
 - STATOR: TIN PLATED

ITEM NO.	DESCRIPTION	DRAWN	DATE
8	新增PCB LAYOUT尺寸	Jack	040720
7	更新RECOMMENDED FFC/FPC DIM.	Jack	010920
6	更新PIN腳項	Jack	052119
5	更新PIN腳項	Jack	120817
4	更新PIN腳項	Jack	101816
3	更新為AO版	Jack	080416
2	更新圖面	Jack	072916
1	更新圖面	Jack	070716

廣東科斯達電子科技有限公司

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 - 15	±0.3
Above 15 - 30	±0.4
Above 30 - 50	±0.5
Angle	±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	04/07/20			
CHECKED BY:	DATE	FINISH	MODLE	FPC 0.5PH H:2.0mm 後掀式
Jacky Chen	04/07/20			
APPROVED BY:	DATE	SCALE	DWG NO.	SIZE
Tony Kao	04/07/20	1:1		A4
		SHEET NO.	PART NO.	VER
		1 of 1		A5