



航模连接器

电气特性

额定电流: 15A

信号针: 1A

耐电压: 500V DC

接触电阻 ≤ 1.2mΩ

绝缘电阻 ≥ 2000MΩ

瞬时电流: &A1min < 80C 30A

温升: 15A 4h < 60C

爬电距离: 1.5mm

				广东科斯达电子科技有限公司 KSDKG Guang dong Keside Electronic Technology Co., Ltd.				DRAWN BY: Ming Ming Zou		DATE: 6/8/23		MAT'L		TITLE: JACK	
								CHECKED BY: Ning Ning Su		DATE: 6/8/23		FINISH		MODLE: TX connector	
				APPROVED BY: Jia Xiang		DATE: 6/8/23		SCALE: 1:1		DWG NO.: KSD-TX-30LX-M		SIZE: A4			
				TOLERANCE UNLESS OTHERWISE STATED:		3RD. ANGEL'S		UNITS: MM		SHEET NO.: 1 of 1		PART NO.:			
				Up to 5 ±0.2								VER: R4			
				Above 5 ~ 15 ±0.3											
				Above 15 ~ 30 ±0.4											
				Above 30 ~ 50 ±0.5											
				Angle ±0.3°											
ITEM NO.	DESCRIPTION	DRAWN	DATE												
4	更新材質	Jack	050420												
3	更新尺寸	Jack	121119												
2	更新尺寸標示位置	Jack	082719												
1	更新尺寸	Jack	080519												