



安装图

SPECIFICATIONS

Current rating : 2.0A AC , DC
 Voltage rating : 100V AC , DC
 Temperature rating : -25°C ~ +85°C
 Insulation resistance : 1,000MΩ min.
 Withstand voltage : 800V AC/minute
 Contact resistance : 20mΩ/Max
 Material:
 Housing : Nylon 66, UL94V-2
 Pin : Brass / Tin-plated
 Contact : Phosphor Bronze

| 位数 | 型号 | 尺寸 | |
|----|------|------|------|
| | | A | B |
| 2 | 2AW | 2.0 | 6.0 |
| 3 | 3AW | 4.0 | 8.0 |
| 4 | 4AW | 6.0 | 10.0 |
| 5 | 5AW | 8.0 | 12.0 |
| 6 | 6AW | 10.0 | 14.0 |
| 7 | 7AW | 12.0 | 16.0 |
| 8 | 8AW | 14.0 | 18.0 |
| 9 | 9AW | 16.0 | 20.0 |
| 10 | 10AW | 18.0 | 22.0 |
| 11 | 11AW | 20.0 | 24.0 |
| 12 | 12AW | 22.0 | 26.0 |

廣東科斯達電子科技有限公司

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao
 DATE: 11/13/12

| | | |
|------------------|----------|-----------|
| MAT'L | TITLE | CONNECTOR |
| FINISH | MODLE | |
| SCALE: 1:1 | DWG NO. | |
| SHEET NO. 1 of 1 | PART NO. | |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|-------|------|
| | | | |
| | | | |
| | | | |