



航模3+7公母座连接器10PIN

KSD-TX-1010系列技术参数

额定电流: 主铜件: 20A

信号针: 5A

耐电压: 500V DC

接触电阻: 主铜件: ≤0.80mΩ

信号针: ≤1.50mΩ

绝缘电阻≥2000MΩ

瞬时电流: &A1min<80C 40A

温升: 主铜件: 20A 4h < 60°C 18#

信号针: 5A 4h < 60°C 26#

爬电距离: 1.6mm

				广东科斯达电子科技有限公司 KSDKG Guang dong Keside Electronic Technology Co., Ltd.				DRAWN BY:	DATE	MAT'L	TITLE	JACK	
4	更新材質	Jack	050420					Ming Ming Zou	6/8/23			FINISH	MODLE
3	更新尺寸	Jack	121119	CHECKED BY:	DATE	SCALE	1:1	DWG NO.	KSD-TX-1010W-G	SIZE			
2	更新尺寸標示位置	Jack	082719							Ning Ning Su	6/8/23	VER	
1	更新尺寸	Jack	080519	APPROVED BY:	DATE	SHEET NO.	1 of 1	PART NO.		R4			
ITEM NO.	DESCRIPTION	DRAWN	DATE							Jia Xiang	6/8/23		

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S

UNITS MM