



RECOMMENDED PCB LAYOUT



Note:

Rating:

- 1.1: Operating Voltage: 50V AC/DC.
- 1.2: Current Rating: 0.5A AC/DC.
- 1.3: Contact Resistance: 30mΩ Max
- 1.4: Insulation Resistance: 500MΩ Min
- 1.5: Operating Temperature: -25°C~+85°C.

Material:

- 1.1 Housing: LCP
- 1.2 Terminal: Phosphor Bronze, Tin plated over Nickel

PIN NO.	DIM.A	DIM.B	DIM.C	PIN NO.	DIM.A	DIM.B	DIM.C
4	6.00	5.10	3.00	19	21.00	20.10	18.00
5	7.00	6.10	4.00	20	22.00	21.10	19.00
6	8.00	7.10	5.00	21	23.00	22.10	20.00
7	9.00	8.10	6.00	22	24.00	23.10	21.00
8	10.00	9.10	7.00	23	25.00	24.10	22.00
9	11.00	10.10	8.00	24	26.00	25.10	23.00
10	12.00	11.10	9.00	25	27.00	26.10	24.00
11	13.00	12.10	10.00	26	28.00	27.10	25.00
12	14.00	13.10	11.00	27	29.00	28.10	26.00
13	15.00	14.10	12.00	28	30.00	29.10	27.00
14	16.00	15.10	13.00	29	31.00	30.10	28.00
15	17.00	16.10	14.00	30	32.00	31.10	29.00
16	18.00	17.10	15.00	31	33.00	32.10	30.00
17	19.00	18.10	16.00	32	34.00	33.10	31.00
18	20.00	19.10	17.00	33	35.00	34.10	32.00

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新尺寸	Jack	091819
1	更新圖面	Jack	052719

**廣東科斯達電子科技有限公司**

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3

3RD. ANGEL'S

UNITS    MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	09/18/19		MODLE	1.0 FPC N/Z 直立式 SMT 正腳位 H:4.5mm
CHECKED BY:	DATE	FINISH	DWG NO.	SIZE
Jacky Chen	09/18/19			A4
APPROVED BY:	DATE	SCALE	PART NO.	VER
Tony Kao	09/18/19	1 : 1		R2
SHEET NO.	1 of 1			