

SPECIFICATIONS:

CONTACT RATING : 5 AMPS / 120V AC or 28V DC

2 AMPS / 250V AC or 0.4VA AMPS @ 20V AC or DC

ELECTRICAL LIFE : 50,000 make-and-break cycles at full load.

CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 VDC

100 mA , for both coin silver and gold plated contacts.

INSULATION RESISTANCE : 1,000 MΩ min

DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.

OPERATING TEMPERATURE : -30°C to 130°C

MATERIALS:

CASE : Dially phthalate (DAP)(UL-94V-0)

ACTUATOR : Brass,chrome plated.

BUSHING : Brass. nickel plated.

HOUSING : Stainless steel.

TERMINAL/CONTACT : Brass , with silver or gold plated.


or gold over silver

SWITCH SUPPORT : Brass , tin plated.

 **广东科斯达电子科技有限公司**
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Frank Wu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao
 DATE: 11/04/11
 DATE: 11/04/11
 DATE: 11/04/11

MAT'L	TITLE	SWITCH
FINISH	MODLE	TOGGLE ROCKER SWITCH
SCALE	DWG NO.	
SHEET NO.	PART NO.	
1 : 1		
1 of 1		

SIZE
 A4
 VER
 A

ITEM NO.	DESCRIPTION	DRAWN	DATE