




REV.	DESCRIPTION	APPROVED BY	DATE	ECN NO.
A	RELEASE	Emily Suen		
B				
C				
D				

1. MATERIAL :
- 1-1. HOUSING : PA66 ; COLOR : BLACK.
- 1-2. CONTACT : BRASS
- 1-3. NUT : BRASS
- 1-4. O-RING : EPDM ; COLOR : BLACK
- 1-5. SHELL : BRASS.
2. FINISH :
- 2-1. CONTACT : GOLD FLASH MICRO INCHES MIN.
- UNDER PLATE : NICKEL
- 2-2. NUT : NICKEL PLATED
- 2-3. SHELL : NICKEL PLATED
3. ELECTRICAL SPECIFICATION :
- 3-1. Rated current :3PIN~8PIN 5A ; 12PIN~14PIN 3A
- 3-2. Rated Voltage :3PIN~8PIN 250V ;12PIN~14PIN 60V
- 3-3. Water proof: IP67
4. Environmental :
- 4-1. Operation Temperature : -40℃~85℃

DI-03F2-16-11	DI-04F2-22-11	DI-05F2-27-11	DI-05F2-19-11	DI-06F2-27-11	DI-07F2-20-11	DI-07F2-19-11	DI-08F2-17-11	DI-12F2-16-11	DI-14F2-02-11

DRAWN	LEO	APP'D	Ku Chou	UNIT	mm	TOLERANCE .x ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGULA ±1°		广东科斯达电子科技有限公司 GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.	TITLE	DIN M16 (F) 後鎖焊線式			
CHK'D	Emily Suen			SCALE	1:1				PART NO.	SEE TABLE A	DWG NO.	QC9400	VERSION A